



## VHF AND UHF TRANSCEIVERS

**IC-F121S** (VHF transceiver)  
**IC-F221S** (UHF transceiver)



- Powerful 50W (VHF), 45W (UHF) Output
- Simple Operation with Large Buttons and Volume Knob
- 4W typ. Front-mounted Speaker
- 8 Memory Channels with LED Display
- Interactive LED Lighting and Flexible Hanger Actions
- Built-in 2-Tone, 5-Tone, CTCSS, DTCS Encoder & Decoder
- Advanced Multi 2-tone/5-tone Systems (See overleaf for details)
- Standard DTMF Encoder and Optional DTMF Decoder with ANI Function
- Programmable Wide/Narrow Channel Spacing for Each Channel
- 2.5kHz Channel Step (U.S.A. VHF only)



Icom Inc.

**ADDITIONAL FEATURES**

**Advanced Multi 2-tone/5-tone systems**

- Programmable actions when a matched tone is received
  - LED lighting ON/OFF/Blink
  - Answer back calls
  - Beep sounds
  - Scan start/stop
  - Auto transmission
  - Stun/Kill functions (prevents use of a lost or stolen radio)
  - External out for horn drive (Optional OPC-617 is required)
- Ten 2-tone codes or eight 5-tone codes can be decoded on a channel
- Three call codes are programmable

**Other features**

- Hook scan function and Hook scan ON/OFF button are assignable
- 24-digit DTMF autodial memory
- Automatic ID (DTMF code) transmission linked to PTT
- Busy lockout and repeater lockout
- Power on password
- External I/O terminal socket with optional OPC-617
- Optional Voice Scrambler, UT-109/UT-110
- Meet MIL-STD 810 C, D, E and F Specification

**SPECIFICATIONS**

**GENERAL**

- Frequency coverage : IC-F121S 136–174MHz  
IC-F221S 440–490MHz
- Number of channels : 8 channels (4 channels × 2 banks)
- Channel spacing : 12.5/25kHz, 15/30kHz
- PLL channel step : VHF 2.5, 3.125kHz  
UHF 5, 6.25kHz
- Frequency stability : VHF ±5.0ppm  
UHF ±2.5ppm
- Operating temp. range : -30°C to +60°C; -22°F to +140°F
- Power supply voltage : 13.6V DC
- Current drain (approx.) : Tx VHF (50W) 14A  
UHF (45W) 13A  
Rx max. audio 1200mA  
standby 300mA
- Antenna impedance : 50Ω (SO-239)
- Dimensions (W×H×D) : 150×40×167.5mm;  
5<sup>29</sup>/<sub>32</sub>×1<sup>16</sup>/<sub>16</sub>×6<sup>19</sup>/<sub>32</sub>in
- Weight : 1.1kg ; 2.4lb

**TRANSMITTER**

- Output power : VHF 50W  
(at 13.6V DC) UHF 45W
- Max. freq. deviation : ±5.0/2.5kHz (wide/narrow)
- Spurious emissions : 70dB typ.
- Adjacent Ch. power : 70/60dB (wide/narrow)
- Mic. impedance : 600Ω (8-pin modular)

**RECEIVER**

- Sensitivity : 0.25μV typ. (at 12dB SINAD)
- Squelch sensitivity : 0.25μV typ.
- Adjacent Ch. selectivity : 75/65dB typ. (wide/narrow)
- Spurious response : 75dB
- Intermodulation : 75dB typ.
- Audio output power : 4W typ. at 10% distortion with a 4Ω load
- Ext. SP connector : 2-conductor 3.5 (d) mm (1/8")/4Ω

**Applicable U.S. Military Specifications**

The IC-F121S/F221S meets MIL-STD requirements and strict environmental standards as follows.

Standard	MIL 810 C		MIL 810 D		MIL 810 E		MIL 810 F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, II
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

**Supplied Accessories**


- Hand mic. (HM-100N)
- DC power cable
- Mounting bracket kit
- Hanger Kit
- Key assign stickers

Measurements made in accordance with EIA-152C/204D, TIA-603. All stated specifications are subject to change without notice or obligation.

**OPTIONS**

Some options may not be available in some countries. Please ask your dealer for details.

- **HM-100TN** DTMF MICROPHONE
- **OPC-617** ACC CABLE  
For external terminal connection.
- **SM-25** DESKTOP MICROPHONE  
Convenient for dispatching, equipped with monitor switch.
- **SP-5/SP-10/SP-22** EXTERNAL SPEAKERS  
Compact and easy-to-install.  
Input impedance: 4Ω; Max. input power: 5W
- **UT-108** DTMF DECODER UNIT  
Provides DTMF decode and ANI capabilities.
- **UT-109** VOICE SCRAMBLER UNIT (Version 02)  
Up to 32 non-rolling scrambling codes available.
- **UT-110** VOICE SCRAMBLER UNIT (Version 02)  
Up to 1020 (255 codes × 4 groups) rolling scrambling codes are available.



Les spécifications et informations données dans ce document peuvent être modifiées sans préavis.

**ICOM FRANCE**

Zac de la Plaine - 1, Rue Brindejonc des Moulinais  
BP 5804 - 31505 TOULOUSE CEDEX  
Tél : 05 61 36 03 03 - Fax : 05 61 36 03 00  
WEB ICOM : <http://www.icom-france.com>  
E-mail : [icom@icom-france.com](mailto:icom@icom-france.com)



CACHET REVENDEUR

